

▶ 84" True 4K2K UHD Display

QD-84



LED 

▶ FEATURES

- LED-backlit technology with UHD 3840 x 2160 resolution
- True 4K2K quality with refresh rates of 60Hz over DisplayPort
- 22.6 mm (right/left) and 25.6 mm (top/bottom)
- Versatile connectivity: HDMI, DisplayPort, VGA, DVI, CVBS, Component
- Daisy chain availability: DisplayPort, RS-232 and IR
- RS-232 looping and RJ45 allow programmable remote control via computer
- IR looping allows easy operation via remote controller during multiple setting
- USB playback: USB plug and select on OSD for media content play function
- OPS slot ready for easy media player integration
- Flexible display orientation: Portrait/Landscape
- VESA mounting compliance
- Installed 8 handles at the rear of the display for easy lifting
- Built-in speakers (10Wx2)
- Durable metal housing design

▶ SPECIFICATION

Panel	Panel Type	LED-Backlit TFT LCD (IPS Panel)
	Panel Size	84"
	Max. Resolution	3840 x 2160 (UHD)
	Pixel Pitch	0.4845 mm
	Brightness	500 cd/m ² (Typical)
	Contrast Ratio	1,400 : 1 (Typical)
	Viewing Angle (H/V)	178°/178°
	Display Colour	1.06 billion
	Response Time	6 ms (GTG)
	Input	VGA
DVI		24-Pin DVI-D
HDMI		1.4 X 3
DisplayPort		X 1
CVBS		RCA (Share with component Y)
Component (YPbPr)		RCA
USB		Type A
OPS	X 1	
Output	DisplayPort	X 1
External Control	RS-232 in/out	Phone Jack 4 pin
	RJ45	RJ45
	IR in/out	3.5Ø Jack
Audio	Audio In	Stereo Mini Jack X 2
	Audio Out	Stereo Mini Jack X 1
	Internal Speaker	10W X 2
	External Speaker	Jack with push button to switch Int / Ext
Power	Power Supply	Internal
	Power Requirements	90 – 240V, 50 – 60Hz
	Consumption	<600W (Max) <0.5W (Standby/Off)
Operating Conditions	Temperature	5°C ~ 40°C (41°F ~ 104°F) Landscape
		5°C ~ 35°C (41°F ~ 95°F) Portrait
	Humidity	10%~90% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	10%~90% (No condensation)
Mounting	VESA FPMPI	Yes (M8*600 x 500 mm)
Dimensions	w/o base (W x H x D)	1910 x 1102 x 77.8 mm (75.2" x 43.4" x 3.1")
	Packaging (W x H x D)	2205 x 1429 x 474 mm (86.8" x 56.3" x 18.7")
Weight	w/o base	70.0 kg (154.3 lbs)
	Packaging	102.5 kg (226 lbs)
Accessories	Supplied	CD ROM (user manual), Power cable, 15-Pin D-sub cable, Remote control, RS-232 cable

All specifications are subject to change without prior notice