

## AXIS M3046-V Network Camera

Quad HD / 4 MP fixed mini dome with HDMI and wide view

AXIS M3046-V is an affordably priced, indoor fixed dome that provides 4 MP video. WDR ensures that details are visible both in dark and bright areas. HDMI support enables live streaming to an HDTV monitor for public viewing. The camera supports video analytics such as people counting. AXIS M3046-V can also be used as an alternative to a camera with varifocal lens – its 4MP resolution and digital PTZ capability enable sharp, cropped out views in HDTV 1080p, for example, with a horizontal field of view between 95° and 128°. No manual focusing is needed since the camera comes factory-focused.

- > **Ultra-compact, vandal- and dust-resistant design**
- > **Digital PTZ and multi-view streaming**
- > **HDMI support enables streaming to a monitor**
- > **Axis' Zipstream technology for reduced bandwidth and storage**
- > **Axis' Corridor format & 3-axis camera angle adjustment**



# AXIS M3046–V Network Camera

<b>Camera</b>	
<b>Image sensor</b>	1/3" progressive scan RGB CMOS
<b>Lens</b>	M12 mount, Fixed iris, Fixed focus 2.4 mm, F2.2 Horizontal field of view: 128° Vertical field of view: 69°
<b>Light sensitivity</b>	0.3 lux at 30 IRE F2.2
<b>Shutter time</b>	1/32500 s to 1/5 s
<b>Camera angle adjustment</b>	Pan ±177°, Tilt ±65°, Rotation ±176° Can be directed in any direction and see the wall/ceiling
<b>Video</b>	
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profiles, Motion JPEG
<b>Resolutions</b>	2688x1520 to 320x240 HDMI 1080p@25/30 fps (50/60 Hz) HDMI 1080i@50/60 fps (50/60 Hz) HDMI 720p@50/60 fps (50/60 Hz) HDMI 720p@25/30 fps (50/60 Hz)
<b>Frame rate</b>	25/30 fps with power line frequency 50/60 Hz
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, Axis' ZIPstream technology in H.264, VBR/MBR H.264 HDMI
<b>Multi-view streaming</b>	Up to 2 individually cropped out view areas in full frame rate streaming
<b>Pan/Tilt/Zoom</b>	Digital PTZ
<b>Image settings</b>	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Backlight compensation, WDR, Text and image overlay, Mirroring of images, Privacy mask Rotation: 0°, 90°, 180°, 270°, including Corridor Format
<b>Network</b>	
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, HDMI 1.4b
<b>System integration</b>	
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at <a href="http://www.onvif.org">www.onvif.org</a>
<b>Analytics</b>	AXIS Video Motion Detection 3, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>
<b>Event triggers</b>	Analytics, Edge storage events
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS network share and email Notification: email, HTTP, HTTPS and TCP and SNMP trap Video recording to edge storage Send video clip Pre- and post-alarm video buffering

	Overlay text
<b>Data streaming</b>	Event data
<b>Built-in installation aids</b>	Pixel counter
<b>General</b>	
<b>Casing</b>	Color: White NCS S 1002-B (For repainting of cover, remove the transparent dome. Contact your Axis partner for repainting instructions), Encapsulated electronics, Captive screws (Torx 10) IP42 water- and dust-resistant (to comply with IP42, follow instructions in Installation Guide), IK08 impact-resistant, polycarbonate/ABS casing
<b>Sustainability</b>	PVC free
<b>Memory</b>	512 MB RAM, 256 MB Flash
<b>Power</b>	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 1 Typical 2.8 W, max 3.2 W
<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE HDMI Type D
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for recording to dedicated network-attached storage (NAS) For memory card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>
<b>Operating conditions</b>	0 °C to 40 °C (32 °F to 104 °F) Humidity 15–85% RH (non-condensing)
<b>Storage conditions</b>	–40 °C to 70 °C (–40 °F to 158 °F) Humidity 15–85% RH (non-condensing)
<b>Approvals</b>	EN 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A and B, ICES-003 Class B, VCCI Class B, RCM A5/NZS CISPR 22 Class B, KCC KN32 Class B, KN35, IEC/EN/UL 60950-1, IEC/EN 60529 IP42, IEC/EN 62262 Class IK08
<b>Dimensions</b>	Height: 56 mm (2.2 in) ø 101 mm (4.0 in)
<b>Weight</b>	180 g (0.40 lb)
<b>Included accessories</b>	Installation Guide, Windows decoder 1-user license, Torx L-key
<b>Optional accessories</b>	AXIS T94 mounts for various installations Black casing Smoked dome Cover view AXIS Surveillance microSDXC™ Card 64 GB
<b>Video management software</b>	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a>
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

- a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)